

CERTIFIED
LUXEON
LUMINAIRE MANUFACTURER



outdoor fixture



indoor fixture

PixelArc R

- 22 high intensity K2 Luxeon emitters
- 1 watt red and amber, 3 watt green and blue LEDs
- 4.29 billion colour combinations
- Beam angle 6° conical as standard
- Holographic diffusers available to vary the output beam angle
- New built in effects generator, capable of more than 1000 effects
- Up to 29 channels of effects control
- Independent DMX start address for the effects generator
- Programmable offset for synchronising effects over multiple fixtures
- DMX 512 digital input/output with 8 or 16 bit RGB and RGBA modes
- Factory reset option
- Control via external source or stand alone master/slave
- Outdoor unit UL listed for wet locations fitted with cable glands for power and data
- Indoor unit fitted with 5 pin XLR connectors for data and trailing lead for power
- Auto setting power input 100 - 250V AC
- Low power consumption (60 watts)
- Convection cooled
- Robust metal construction
- Black anodised as standard, other colours available to order
- Dimensions 270mm x 344mm x 127mm
- Weight complete 7.3kg LED housing 3.4kg Control housing 3.4kg

Preliminary specification - subject to change without notice



CERTIFIED
LUXEON
LUMINAIRE MANUFACTURER



outdoor fixture



indoor fixture

PixelArc C

- 44 high intensity K2 Luxeon emitters
- 1 watt red and amber, 3 watt green and blue LEDs
- 4.29 billion colour combinations
- Beam angle 6° conical as standard
- Holographic diffusers available to vary the output beam angle
- New built in effects generator, capable of more than 1000 effects
- Up to 29 channels of effects control
- Independent DMX start address for the effects generator
- Programmable offset for synchronising effects over multiple fixtures
- DMX 512 digital input/output with 8 or 16 bit RGB and RGBA modes
- Factory reset option
- Control via external source or stand alone master/slave
- Outdoor unit UL listed for wet locations fitted with cable glands for power and data
- Indoor unit fitted with 5 pin XLR connectors for data and trailing lead for power
- Auto setting power input 100 - 250V AC
- Low power consumption (100 watts)
- Convection cooled
- Robust metal construction
- Black anodised as standard, other colours available to order
- Dimensions 270mm x 432mm x 127mm
- Weight complete 7.3kg LED housing 3.4kg Control housing 3.4kg

Preliminary specification - subject to change without notice





PixelLine Micro W

- 22 high intensity K2 Luxeon emitters
- 1 watt red and amber, 3 watt green and blue LEDs
- 4.29 billion colour combinations
- Beam angle 6° conical as standard
- New built in effects generator, capable of more than 1000 effects
- Up to 29 channels of effects control
- Independent DMX start address for the effects generator
- Programmable offset for synchronising effects over multiple fixtures
- DMX 512 digital input/output with 8 or 16 bit RGB and RGBA modes
- Provides an alternative projection medium for video manipulation software
- Factory reset option
- Control via external source or stand alone master/slave
- PowerCon 20 Amp chassis mounted input and output sockets fitted as standard
- Auto setting power input 100 - 250V AC
- Yoke supplied as standard for ease of hanging or floor standing
- Low power consumption (60 watts) virtually no heat generated
- Internal quiet fan cooling system
- Robust metal construction
- Black powder coating as standard, other colours available to order
- Dimensions 205mm (L) x 84mm (H) x 167mm (D) - 155mm (H) with yoke
- Weight 2.2kg with yoke (1.9kg without)
- IP20 rated

Preliminary specification - subject to change without notice



CERTIFIED
LUXEON
LUMINAIRE MANUFACTURER

Code	Description
PLMBW	PixelLine Micro Wash
PLMBY	PixelLine Micro yoke



Pixel RANGE

PixelLine Micro E

- 174 high intensity red, green and blue LEDs
- 16.7 million colour combinations
- Beam angle 20° conical as standard
- New built in effects generator, capable of more than 1000 effects
- Up to 29 channels of effects control
- Independent DMX start address for the effects generator
- Programmable offset for synchronising effects over multiple fixtures
- DMX 512 digital input/output with 3 or 9 channel RGB mode
- Provides an alternative projection medium for video manipulation software
- Factory reset option
- Control via external source or stand alone master/slave
- PowerCon 20 Amp chassis mounted input and output sockets fitted as standard
- Auto setting power input 100 - 250V AC
- Yoke supplied as standard for ease of hanging or floor standing
- Low power consumption (25 watts) virtually no heat generated
- Silent convection cooling system
- Robust metal construction
- Black powder coating as standard, other colours available to order
- Dimensions 205mm (L) x 84mm (H) x 167mm (D) - 155mm (H) with yoke
- Weight 2.4kg with yoke (1.9kg without)
- IP20 rated

Preliminary specification - subject to change without notice



Code	Description
PLMBE	PixelLine Micro Effect
PLMBY	PixelLine Micro yoke